

Specifications XPA U 358 Series

Audio

| | |
|----------------------|-------------------------|
| Voltage gain | |
| XPA U 358..... | 14x (23 dB) |
| XPA U 358-70V | 57x (35 dB) |
| XPA U 358-100V | 81x (38 dB) |
| CMRR..... | 75 dB (typical) @ 1 kHz |

Audio Input

| | |
|---------------------------------------|--|
| Number/signal type | 8 balanced/unbalanced |
| Connectors..... | (4) 3.5 mm captive screw connector, 5-pole |
| Impedance | >10k ohms balanced/unbalanced, DC coupled |
| Nominal level | +4 dBu, balanced |
| Maximum level | +20 dBu, balanced |
| Input sensitivity | +4 dBu |
| Input signal detection threshold..... | -65 dBu ±3 dB, balanced |

NOTE: 0 dBu = 0.775 Vrms, 0 dBV = 1 Vrms, 0 dBV ≈ 2 dBu

Audio Output

| | |
|----------------------|---|
| Number/signal type | |
| XPA U 358..... | 8 channels, 4 or 8 ohms |
| XPA U 358-70V | 8 channels, 70V |
| XPA U 358-100V | 8 channels, 100V |
| Connectors..... | (4) 5 mm screw-lock captive screw connector, 4-pole |

NOTE: These connectors accept wires of 22 AWG to 12 AWG.

Load impedance

| | |
|----------------------|------------------|
| XPA U 358..... | 4 ohms minimum |
| XPA U 358-70V | 143 ohms minimum |
| XPA U 358-100V | 286 ohms minimum |

Amplifier type

Class D

Output power

| | |
|----------------------|---|
| XPA U 358..... | 35 watts rms per channel, 4 ohms, 1 kHz, 0.1% THD |
| | 35 watts rms per channel, 8 ohms, 1 kHz, 0.1% THD |
| XPA U 358-70V | 35 watts rms per channel, 70V, 1 kHz, 0.1% THD |
| XPA U 358-100V | 35 watts rms per channel, 100V, 1 kHz, 0.1% THD |

Frequency response

20 Hz to 20 kHz, ±1 dB

THD + Noise

0.1% @ 1 kHz at 3 dB below clipping

S/N

100 dB, 20 Hz - 20 kHz, unweighted

Damping factor

| | |
|----------------------|-----------------|
| XPA U 358..... | >100 @ 8 ohms |
| XPA U 358-70V | >100 @ 143 ohms |
| XPA U 358-100V | >100 @ 286 ohms |

Specifications • XPA U 358 Series (Continued)

High pass filter

- XPA U 358-70V 80 Hz, 12 dB per octave rolloff, selectable via captive screw
- XPA U 358-100V 80 Hz, 12 dB per octave rolloff, selectable via captive screw

Control/remote — amplifier

Control port

- XPA U 358..... (1) 3.5 mm captive screw, 2-pole
- XPA U 358-70V (2) 3.5 mm captive screw, 2-pole
- XPA U 358-100V (2) 3.5 mm captive screw, 2-pole

Pin configurations

- | | |
|---|------------------------------|
| Standby power control (contact closure) | Pin 1 = GND, pin 2 = Standby |
| High pass filter (contact closure) | Pin 1 = GND, pin 2 = OFF |

General

Power supply Internal
Input: 100 VAC - 240 VAC, 50-60 Hz

Power consumption and thermal dissipation

XPA U 358-70V

| | | 115 VAC, 60Hz | | | | 230 VAC, 50Hz | | | |
|--|-----------|-----------------|-------------------|---------------------|--------|-----------------|-------------------|---------------------|--------|
| | | AC Line Current | AC Power Consumed | Thermal Dissipation | | AC Line Current | AC Power Consumed | Thermal Dissipation | |
| Condition | | A | W | W | BTU/hr | A | W | W | BTU/hr |
| Active (1/8 power), all channels driven | 8Ω | 0.5 | 50.0 | 15.0 | 51 | 0.3 | 48.7 | 13.7 | 47 |
| | 4Ω | 0.5 | 52.6 | 17.6 | 60 | 0.3 | 50.7 | 15.7 | 54 |
| Quiescent (idle) | | 0.1 | 8.5 | 8.5 | 29 | 0.2 | 8.2 | 8.2 | 28 |
| Standby | | <0.1 | <1 | <1 | <3 | <0.1 | <1 | <1 | <3 |

XPA U 358-70V

| | | 115 VAC, 60Hz | | | | 230 VAC, 50Hz | | | |
|--|------------|-----------------|-------------------|---------------------|--------|-----------------|-------------------|---------------------|--------|
| | | AC Line Current | AC Power Consumed | Thermal Dissipation | | AC Line Current | AC Power Consumed | Thermal Dissipation | |
| Condition | | A | W | W | BTU/hr | A | W | W | BTU/hr |
| Active (1/8 power), all channels driven | 70V | 0.5 | 54.5 | 19.5 | 67 | 0.3 | 53.3 | 18.3 | 62 |
| | | 0.1 | 9.0 | 9.0 | 31 | 0.2 | 8.8 | 8.8 | 30 |
| Standby | | <0.1 | <1 | <1 | <3 | <0.1 | <1 | <1 | <3 |

Specifications • XPA U 358 Series (Continued)

XPA U 358-100V

| | | 115 VAC, 60Hz | | | | 230 VAC, 50Hz | | | |
|---|------|-----------------|-------------------|---------------------|--------|-----------------|-------------------|---------------------|--------|
| | | AC Line Current | AC Power Consumed | Thermal Dissipation | | AC Line Current | AC Power Consumed | Thermal Dissipation | |
| Condition | | A | W | W | BTU/hr | A | W | W | BTU/hr |
| Active (1/8 power), all channels driven | 100V | 0.5 | 55.7 | 20.7 | 71 | 0.3 | 54.4 | 19.4 | 66 |
| Quiescent (idle) | | 0.1 | 9.6 | 9.6 | 33 | 0.2 | 9.5 | 9.5 | 32 |
| Standby | | <0.1 | <1 | <1 | <3 | <0.1 | <1 | <1 | <3 |

Temperature/humidity

| | |
|-------------------------------------|--|
| Storage | -40 to +158°F (-40 to +70°C) / 10% to 90%, non-condensing |
| Operating | +32 to +122°F (0 to +50°C) / 10% to 90%, non-condensing |
| Cooling..... | Convection, no vents |
| Protection | Clip limiting, thermal, short circuit, DC output |
| Indication | Limiter/Protect LED indicates the onset of clip limiting, thermal cycling, or a short circuit. Over Temp LED indicates when the amplifier exceeds the recommended operating temperature for optimal unit longevity. Power LED indicates power state, DC output protection (see XPA Ultra Series User Guide for details). |
| Rack mount | Yes, with included mounting brackets or optional rack shelf |
| Enclosure..... | Metal |
| Enclosure dimensions | 1.7" H x 8.7" W x 10.5" D (1U high, half rack wide) 43 mm H x 220 mm W x 267 mm D |
| Product weight | 4.2 lbs (1.9 kg) |
| Regulatory compliance..... | CE, CEC, CISPR 22 Class B, C-tick, CUL, ENERGY STAR®, European Code of Conduct, FCC Class B, ICES, KC, RoHS, UL, UL 2043, VCCI Class B |
| Product warranty | 3 years parts and labor |
| Everlast power supply warranty..... | 7 years parts and labor |

NOTE: All nominal levels are at ±10%.

NOTE: Specifications are subject to change without notice.

NOTE: Shipping weights and dimensions are available at www.extron.com.

5623-D3